



9 mm PMI® Sewn Eye



PMI® uses precision stitching to create a permanent, sewn termination that is stronger than any knotted termination and nearly as strong as the rope itself. Heat shrink tubing protects the stitching and the label from abrasion. Add these NFPA 2500 (2022) certified terminations to the [9 mm PMI® EZ Bend™ Hudson Classic Professional Rope](#). Also available for [10 mm](#), [11 mm](#) or [12.5 mm](#) PMI® Hudson Classic Professional EZ-Bend™ ropes.

Key Features

- Streamlined permanent termination
- No knots
- Nearly as strong as the rope
- Stronger than knots
- Two separate but equal blocks of stitching provide greater safety

Additional Information

Shipping weight | N/A

of Ends | One End, Two Ends

Brand | [PMI](#)

Compliant | NFPA 2500 (1983) 2022 ED (E) (WITH 9 MM PMI® HUDSON CLASSIC PROFESSIONAL ONLY)

Diameter | 9 mm

MBS | 14 kN (3,147 lbf —PMI® Hudson Classic Pro EZ)

Tags

[Arborist](#), [Fall protection](#), [Made in USA](#), [Rope Access](#), [Ropes Course](#), [Tower](#)

Product Code

KT36088 | One End

KT36089 | Two Ends

