




TOUCH
SCREEN



ANSI/ISEA 105



EN388



4X32F



UPF
100



STANDARD
100
SHEDDING
TESTED



SPECIFICATIONS:

- **Liner Materials:** 18g Gray Kyorene[®] Pro Graphene A6 Liner
- **Coating Materials:** Black HCT[®] MicroFoam Nitrile
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 00-867

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	2X
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ
CASE WEIGHT	22.03 lbs	22.25 lbs	25.77 lbs	27.09 lbs	29.07 lbs	33.48 lbs

PERFORMANCE LEVEL:

EN388: 4X32F

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

ATTRIBUTES:

- 18g Gray Kyorene[®] Pro Graphene A6 Liner
- Black HCT[®] MicroFoam Nitrile Palm Coating

FEATURES:

- Silicone free
- Touchscreen compatible
- Back of hand TPV protection
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

APPLICATIONS:

- Oil & gas
- Mining
- Construction

CATEGORY:

- Kyorene[®] Pro

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

KYORENE[®]
PRO GRAPHENE

HCT[®]
HCT[®]

Hybrid Coating Technology



VERIFIED GRAPHENE[®]
PRODUCER
THE GRAPHENE COUNCIL

 **ARMOR GUYS**