

K-Series®

Ceros® safety helmet earmuffs



Ergonomic design meets style and convenience. The K-Series® for Ceros® safety helmets include Click-and-Go® magnetic, mechanical, and slot-adapted earmuff options for a simple, convenient accessory attachment option.



- 1 Slot adapted earmuffs
- 2 Click-and-Go® magnetic earmuffs
- 3 Earmuffs designed to work seamlessly with face shield
- 4 Lightweight with length adjustment options for various head shapes
- 5 Snug-fitting, soft foam ear cushions adapt to the surface and head shape of the wearer
- 6 360-degree rotation to nest tightly against Ceros® safety helmets

Accessory compatibility

Helmet accessories

Product Name	Part #	with and without Mips®							
		XP250	XP250E	XP300	XP300E	XP450A	XP450AE	XT400	XT400E
K1C earmuffs	17-15001	◊	◊ [□]			◊	◊ [□]	◊	◊ [□]
K2C earmuffs	17-16001	◊	◊ [□]			◊	◊ [□]	◊	◊ [□]
K2C Full Brim earmuffs	17-16002			◊	◊				

Face shield accessories

Product name	Part #	XP Mechanical	XP Magnetic	XA Magnetic	Ultrex®1
K2M earmuffs ⁺	17-17002 [†]	◊			◊
K2M magnet earmuffs ⁺	17-18002 [†]		◊	◊	

*Requires a face shield or adapter purchase

[□]Warning: earmuffs are not dielectric

◊ = Compatible

Earmuff accessories

Product name	Part #	K1C	K2C	K2C full brim	K2M	K2M Magnetic	K1	K2	K3
Earmuff hygiene kit type 1	17-28001 [†]	◊					◊		
Earmuff hygiene kit type 2	17-29001 [†]		◊	◊	◊	◊		◊	◊

REACH

COMPLIANT † REACH compliant for being skin-safe and void of harsh chemicals

Engineered in Germany Assembled in USA

K-Series®

Ceros® safety helmet earmuffs




Use with face shield

K2M earmuffs

17-17002

ANSI S3.19-1974	Z94.2-2014	EN 352-1
NRR 25 dB	CSA Class A	SNR: 30 dB, H: 35 dB, M: 27 dB, L: 20 dB

- Compatible with mechanical face shield




K2M magnet earmuffs

17-18002

ANSI S3.19-1974	Z94.2-2014	EN 352-1
NRR 24 dB	CSA Class A	SNR: 30 dB, H: 35 dB, M: 27 dB, L: 20 dB

- Compatible with magnetic face shield



Use without face shield – slot adapted

K1C earmuffs

17-15001

ANSI S3.19-1974	Z94.2-2014
NRR 22 dB	CSA Class B
EN 352-1	
SNR: 27 dB, H: 32 dB, M: 24 dB, L: 17 dB	



K2C earmuffs

17-16001

ANSI S3.19-1974	Z94.2-2014
NRR 25 dB	CSA Class A
EN 352-1	
SNR: 30 dB, H: 35 dB, M: 27 dB, L: 20 dB	



K2C full brim earmuff

17-16002

ANSI S3.19-1974
NRR 25 dB

Coming soon



Call **1.877.MY ARMOR** or visit **hexarmor.com**

Protective devices do not provide unlimited protection. Some operations may require machine guards, face shields, special filter lenses, or other safety equipment. Safety helmets do not provide complete protection against hazards, and should only be used in conjunction with the prescribed safety equipment for the application as well as defined safety practices.

UVEX SAFETY GROUP GmbH & Co. KG, parent company of HexArmor®, has achieved a Gold EcoVadis Rating, placing us in the top 5% of sustainable suppliers globally.

